



Complete Mounting & Racking System for All Roof Types

QRail™ System

Product	Description	Ordering Part Number	
		Item Code	Mill Black
 <p>QRail™ Series QMR-RL- Light QMR-RS- Standard QMR-RH- Heavy</p>	QRail Series available in Light, Standard & Heavy rails and in 14ft (168in) or 17.3ft (208in) lengths.	QMR-RL14 (light)	800 805
		QMR-RL17.3 (light)	801 806
		QMR-RS14 (standard)	810 815
		QMR-RS17.3 (standard)	811 816
		QMR-RH14 (heavy)	820 825
		QMR-RH17.3 (heavy)	821 826
 <p>QRsplice™ Internal Splice QMR-ISL- Light QMR-ISS- Standard QMR-ISH- Heavy</p>	Internal splices available for Light, Standard & Heavy QRails. Tool-free installation, integrated bonding, & structural.	QMR-ISL (light)	830 n/a
		QMR-ISS (standard)	831 n/a
		QMR-ISH (heavy)	832 n/a
 <p>QRsplice™ External Splice QMR-ESS- Standard QMR-ESH- Heavy</p>	External splices available for Standard & Heavy QRails.	QMR-ESS (standard)	834 n/a
		QMR-ESH (heavy)	835 n/a
 <p>End Caps QMR-CPL- Light QMR-CPS- Standard QMR-CPH- Heavy</p>	End Caps available for Light, Standard, & Heavy QRails.	QMR-CPL (light)	n/a 885
		QMR-CPS (standard)	n/a 886
		QMR-CPH (heavy)	n/a 887
 <p>Universal Bonded Mid Clamps with QClick™ Technology QMR-UMC</p>	Universal Mid Clamp with QClick Technology available in 30-45mm & 38-50mm sizes. Hardware is pre-assembled.	QMR-UMC3045BP 1.2	872 877
		QMR-UMC3850BP 1.2	873 878
 <p>Universal End Clamps with QClick™ Technology QMR-UE</p>	Universal End Clamp with QClick Technology available in 30-45mm & 38-50mm sizes and with optional bonding clip. Hardware is pre-assembled.	QMR-UEC3045	860 865
		QMR-UEC3850	861 866
		QMR-UEC3045BP	862 867
		QMR-UEC3850BP	863 868

All hardware included. All exposed hardware stainless steel. Additional hardware kits available. Twenty-five (25) year warranty on all products listed.

QRail™ Accessories

Product	Description	Item Code	Ordering Part Number
 <p>T-Bolt QMR-TB</p>	T-Bolt and nut. Engagement indication line on bolt must be vertical to show the bolt is fully engaged in the t-bolt channel.	QMR-TB	stainless steel 880
			Mill Black
 <p>L-Foot QMC-LF</p>	Available in mill or black.	QMC-LF	692 693
			Mill Black
 <p>Grounding Lug QMR-GL</p>	Pre-assembled lay-in lug. Engagement indication line on bolt must be vertical to show the bolt is fully engaged in the t-bolt channel.	QMR-GL	890
			Mill Black
 <p>Wire Clip QMR-WC</p>	Wire clip for PV or trunk cables.	QMR-WC	stainless steel 892
			Mill Black
 <p>WEBB BMC QMR-ECW</p>	Optional WEBB BMC for use with End-Clamps.	QMR-ECW	stainless steel 891
			Mill Black

